

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 September 2001 (27.09.2001)

PCT

(10) International Publication Number
WO 01/70470 A1

(51) International Patent Classification⁷: B26D 3/10

[FR/FR]; 23, rue du 14eme Zouave, F-59251 Al-lennes-Les-Marais (FR). **DELATTRE, Jean-Yves** [FR/FR]; 340, rue Jeunesse, F-59134 Fournes-en-Weppe (FR). **FREYCON, Bernard** [FR/FR]; 12, rue de Wahagnies, F-59239 La Neuville (FR).

(21) International Application Number: PCT/US01/09103

(74) Agents: **OBERHOLTZER, Steven, L.** et al.; Brinks, Hofer, Gilson & Lione, P.O. Box 10395, Chicago, IL 60610 (US).

(22) International Filing Date: 22 March 2001 (22.03.2001)

(81) Designated State (national): US.

(25) Filing Language: English

(84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

(26) Publication Language: English

Published:
— with international search report

(30) Priority Data: 00/03668 22 March 2000 (22.03.2000) FR


For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(71) Applicant (for all designated States except US): VIS-TEON GLOBAL TECHNOLOGIES, INC. [US/US]; Suite 728, Parklane Towers East, 1 Parklane Boulevard, Dearborn, MI 48126 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): SAELEN, Marc

(54) Title: THREE KNIVES CUTTING



WO 01/70470 A1

(57) Abstract: The invention relates to a process and a device for producing a contour of a planiform piece, intended, in particular, for the internal trim of motor vehicles, in which said piece (1) is cut to define at least an apex (2) of said contour (3), having a given profile P, and a side (4), or so-called first side, of said contour (3) extending from said apex (2). According to the invention, there are carried out sequentially: on one hand, cutting of said piece (1) to produce simultaneously at least said apex (2), according to said profile P, and to cut said first side (4) over a portion, referred to as a fraction F, of its length extending from said apex (2); on the other hand, at least another operation of cutting said piece (1) to produce said first side (4), including at least a portion at least of said fraction F.